REGEIVED CENTRAL FAX CENTER

APR 0 9 2007

Applicant: Patrice Flaherty Application No: 10/630,402 Filing Date: 07/30/2003 Attorney Docket No: 1066

IN THE CLAIMS

Please cancel claim 8.

Please amend claims 1, 7 and 24 as follows.

1. (Currently amended) A device for collecting blood from and administering medical fluids to a patient, comprising:

a main tubing segment for conveying the blood and the medical fluids;

an indicator unit and a syringe port disposed in fluid communication with said main tubing segment in branched relationship to said main tubing segment and each other, said indicator unit adapted for indicating blood content volume;

a clamp operably engaging said main tubing segment and adapted o selectively block and unblock said main tubing segment; and

at least one air-permeable membrane provided in said indicator unit.

- 2. (Original) The device of claim 1 further comprising a blood volumeter provided in said indicator unit.
 - 3. (Original) The device of claim 1 wherein said indicator unit is disposed

FAX NO. 3187973063

Applicant: Patrice Flaherty Application No: 10/630,402 Filing Date: 07/30/2003 Attorney Docket No: 1066

in removable fluid communication with said main tubing segment.

4. (Original) The device of claim 3 further comprising a blood volumeter

provided in said indicator unit.

5. (Previously presented) The device of claim 2 wherein said blocd

volumeter is a volumeter chamber.

6. (Original) The device of claim 5 wherein said indicator unit is disposed

in removable fluid communication with said main tubing segment.

7. (Currently amended) A device for collecting blood from and

administering medical fluids to a patient, comprising:

a main tubing segment for conveying the blood and the medical

fluids;

an indicator unit and a syringe port disposed in fluid communication

with said main tubing segment in branched relationship to each other, said indicator

unit adapted for indicating blood content volume and said indicator unit and said

syringe port defining branched bidirectional fluid flow pathways;

a clamp operably engaging said main tubing segment for selectively

-3-

Applicant: Patrice Flaherty Application No: 10/630,402 Filing Date: 07/30/2003

Attorney Docket No: 1066

blocking said main tubing segment; and

at least one air-permeable and liquid-impermeable membrane provided in said indicator unit at a distal end of said indicator unit and allowing bidirectional fluid movement between said indicator unit and said syringe port.

- 8. (Original) The device of claim 7 further comprising a blood volumeter provided in said indicator unit.
- 9. (Original) The device of claim 7 wherein said indicator unit is disposed in removable fluid communication with said main tubing segment.
- 10. (Previously presented) The device of claim 8 wherein said blocd volumeter is a volumeter chamber.
- 11. (Original) The device of claim 10 wherein said indicator unit is disposed in removable fluid communication with said main tubing segment.
- 12. (Withdrawn) A device for collecting blood from and administering medical fluids to a patient, comprising:
 - a main tubing segment for conveying the blood and the medical

fluids;

an indicator unit and a syringe port disposed in fluid communication with said main tubing segment in branched relationship to each other, said indicator unit adapted for indicating blood content;

a blood reservoir provided in fluid communication with said indicator unit; and

a clamp operably engaging said main tubing segment for selective y blocking said main tubing segment.

- 13. (Withdrawn) The device of claim 12 further comprising a blood volumeter provided in said indicator unit.
- 14. (Withdrawn) The device of claim 12 wherein said indicator unit is disposed in removable fluid communication with said main tubing segment.
- 15. (Withdrawn) The device of claim 13 wherein said blood volumeter is a spiral tubing volumeter, a folded tubing volumeter or a volumeter chamber.
- 16. (Withdrawn) The device of claim 12 further comprising a protective container provided in fluid communication with said indicator unit and wherein

said blood reservoir is contained in said protective container.

17. (Withdrawn) A device for collecting blood from and administering medical fluids to a patient, comprising:

a main tubing segment for conveying the blood and the medical fluids;

an indicator unit and a first syringe port disposed in fluid communication with said main tubing segment in branched relationship to each other, said indicator unit adapted for indicating blood content;

a second syringe port provided in fluid communication with said indicator unit; and

a clamp operably engaging said main tubing segment for selectively blocking said main tubing segment.

- 18. (Withdrawn) The device of claim 17 further comprising a cap device for removably engaging and sealing said second syringe port and an air-permeable membrane carried by said cap device.
- 19. (Withdrawn) The device of claim 17 further comprising a blood volumeter provided in said indicator unit.

- 20. (Withdrawn) The device of claim 19 wherein said blood volumeter is a spiral tubing volumeter, a folded tubing volumeter or a volumeter chamber.
- 21. (Withdrawn) A device for collecting blood from and administering medical fluids to a patient, comprising:
- a main tubing segment for conveying the blood and the medical fluids;
- a syringe port provided in fluid communication with said main tubing segment;

an expandible blood receptacle for removably engaging said syringe port in fluid communication with said main tubing segment; and

- a clamp operably engaging said main tubing segment for selectively blocking said main tubing segment.
- 22. (Withdrawn) The device of claim 21 further comprising a blood volumeter provided in fluid communication with said main tubing segment.
- 23. (Withdrawn) The device of claim 21 further comprising a second syringe port provided in fluid communication with said main tubing segment and wherein said syringe port and said second syringe port branch separately from said

main tubing segment.

24. (Currently amended) A device for collecting blood from and administering medical fluids to a patient, comprising:

a main tubing segment for conveying the blood and the medical fluids;

an indicator unit and a port disposed in fluid communication with said main tubing segment in branched relationship to said main tubing segment and each other, said indicator unit having a blood volumeter adapted for indicating blood content volume and said indicator unit and said port defining branched fluid flow pathways;

a clamp operably engaging said main tubing segment and adapted to crimp and selectively block and unblock said main tubing segment; and

at least one air-permeable membrane provided in said indicator unit in fluid communication with said blood volumeter, said blood volumeter disposed between said main tubing segment and said at least one air permeable membrane; and

wherein said at least one air-permeable membrane alloys bidirectional fluid movement between and through said indicator unit and said syringe port.

APR-9-07 MON 5:34 PM JOHN HARRISON FAX NO. 3187973063 P. 9

Applicant: Patrice Flaherty

Application No: 10/630,402

Filing Date: 07/30/2003

Attorney Docket No: 1066

25. (Previously presented) The device of claim 24 further comprising a

connector provided in fluid communication with said main tubing segment and

wherein said indicator unit is disposed in removable fluid communication with said

connector.

26. (Previously presented) The device of claim 24 wherein said blocd

volumeter is a volumeter chamber.

27. (Previously presented) The device of claim 24 further comprising a

collector conduit provided in fluid communication with said main tubing segment

and wherein said indicator unit is disposed in fluid communication with said

collector conduit.

28. (Previously presented) The device of claim 27 wherein said indicator

unit comprises a volumeter conduit provided in fluid communication with said

collector conduit and wherein said blood volumeter is provided in fluid

communication with said volumeter conduit.

29. (Previously presented) The device of claim 28 further comprising a port

disposed between said collector conduit and said volumeter conduit.

-9-

- 30. (Previously presented) The device of claim 24 further comprising a syringe tubing segment provided in fluid communication with said main tubing segment and wherein said port is provided on said syringe tubing segment.
- 31. (Previously presented) The device of claim 24 further comprising a connector provided in said main tubing segment between said clamp and said indicator unit and said port.
- 32. (Previously presented) The device of claim 1 further comprising a tubing bifurcation having a syringe leg and a collector tubing leg communicating with said main tubing segment and wherein said syringe port communicates with said syringe leg; and said indicator unit communicates with said collector tubing leg.